Dhr. Chris Heynen HEYNEN SYSTEMS BV Staalstraat 31 NL-8211 AH LELYSTAD NEDERLAND

your delivery of 2008-05-29

your reference

our reference PVH/10705 date

Zwijnaarde, 2008-11-24

Analysis Report 63346/B

Required tests:

BS 6807:2006, Clause 9 - ignitability of mattresses Ignition source 5 : pine wood crib, top ignition

Identification	Information given by the chient	Date of receipt
number	· ·	
T805810	Circular knitting, 100% polyester yarn, 78dtex, 8 gauge	2008-06-02

Pros Van Hoeyland order responsible

For further information, please contact our sectorial adviser Pros Van Hoeyland

This report runs to 2 pages and may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel. The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.



our reference	date	page
PVH/10705	2008-11-24	2/2

Reference: T805810 - Circular knitting, 100% polyester yarn, 78dtex, 8 gauge

BS 6807:2006, Clause 9 - ignitability of mattresses Ignition source 5: pine wood crib, top ignition

The following test results relate only to the ignitability of the combination of materials under the particular condition of test; they are not intended as a means of assessing the full potential fire hazard of the item in use.

End of tests: 17 June 2008

Deviations from the standard procedure

The composition of the finished mattress is not known, therefore the test specimen is composed of the cover material as received and a foam filling. The test is carried out only on the flat portion of the upper surface.

A. Materials tested

Cover : - quality Circular knitting, 100% polyester yarn, 78dtex, 8 gauge no

Filling : - quality Dumosafe CM33 (Dumo) * fire retardant ± 33 kg/m³ 450 mm x 450 mm x 150 mm

B. Test results - crib 5 on top of the test specimen

	test 1	test2
Flaming criteria		
- unsafe escalating combustion	no	no
- test assembly consumed	no	no
- flames to extremities	no	no
- flames through thickness	no	no
- flame time >10 min	no	no
flame time	2 min 46 s	2 min 58 s
Smouldering criteria		
- unsafe escalating combustion	no	no
- test assembly consumed	no	no
- smoulders to extremities	no	no
- smoulders through thickness	no	no
- smoke/heat/glowing more than 60 min	no	no
- smoulders more than 100 mm from source	no	no
	non-ignition	non-ignition

Conclusion: non-ignition

^{*} The filling complies with schedule 1 part 1 of the UK Furniture and Furnishings (Fire) (Safety) Regulations 1988

Performed under accreditation in the fire lab under the responsibility of Pros Van Hoeyland.